



HARDENER 324

GENERAL DATA	DESCRIPTION	This product is used for the photo emulsion hardening	
	CODE	VXHR832K1	
	PACKAGE	1 Kg	
	FEATURES		Ready to use
			Transparent colour
			It makes the photo emulsions standing on the screen
			It allows to increase the chemical-mechanical resistances of the photo emulsions
		It is not suitable for Nylon fabrics	

INSTRUCTIONS	
	<p>Harden the screen through a sponge or a soft brush, when the photo emulsion is completely dry. Completely and uniformly dampen the two sides of the screen. Let the product work during:</p> <ul style="list-style-type: none"> • 6-12 hours at room temperature • 1 hour at 50°C into oven <p>Once the photo emulsion is hardened, abundantly rinse the screens with water, before using them.</p>

STORAGE	
	<p>Keep the product in its original package, in a sheltered room, at a temperature of 5°C to 35°C.</p>

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk. While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.