

Poligrip PP

Code M490002L001000

PRODUCT DESCRIPTION

Liquid primer with anchoring function for screen printing inks onto polyolefinic materials.

APPLICATION FIELDS

This product is to be used when it is not possible to treat the substrate through flaming or Corona discharge.

APPLICATION PROCESS

| | |
|--------------------------|--|
| Substrates | POLYOLEFINIC MATERIALS (PE – PP) |
| Application | Manual or spray |
| Drying | Room temperature or a few minutes at 50-60°C |
| Storage | If kept in a dark place, in its original sealed package, at a temperature of 15-30°C, the product has a shelf-life of about 2 years. |
| Packaging | 1 L |
| Safety data sheet | Available upon request |

PREPARATION

This product is ready to use and it has to be applied onto the substrate directly, through a cloth or a spray gun.

An application of a regular quantity of product is enough: do not apply an exceeding thickness, that may compromise the adhesion of the subsequently used screen printing inks.

WARNING

This technical data sheet does not replace either the Safety Data Sheet or the specific Conformity Declaration. These documents may be required to our SHEQ (Product safety office), at the following e-mail address: safety@eptainks.com

The technical data sheet does not relieve the printer, who remains the only responsible of the respect of the regulations, the specifications and the related required certifications of the finished items.

TECHNICAL FEATURES

Poligrip PP helps adhesion of screenprinting inks to the substrate, when it is not possible to treat it through flaming or Corona discharge. This product may also be applied onto irregular surfaces or not completely flat.

GENERAL FEATURES

- Primer for polyolefinic materials
- It improves surface tension

SPECIAL RECOMMENDATIONS

- Always test the characteristics of the product, before starting production.
- The above information is the result of previous knowledge and experience; it is neither a guarantee or an assurance.
- When beginning printing, always check the right surface tension.

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us of the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.