



STRIPPER 803 PASTA

GENERAL DATA	DESCRIPTION	This products removes the ghost images after the recovery of the screens	
	CODE	VXGH803K1	
	PACKAGE	1 Kg	
	FEATURES		Ready to use
			Solvent free
			High efficacy in the removal of the ghost images
			It is indicated both for Nylon and polyester fabrics
		It may be used together with STRIPPER 805 SOL (code VXST805K1)	

INSTRUCTIONS	
	<p>This product is ready to use. It is recommended to mix it before use.</p> <p>Apply STRIPPER 803 PASTA through a sponge on the areas of the screens to be treated. Let it work during about 15 - 20 minutes. The working time depends on the fabric conditions: the higher is the halation, the longer is the working time. In any case, it has not to last longer than 60 minutes. The combined action of STRIPPER 803 PASTA and STRIPPER 805 SOL is even more effective than the use of the single products. Remove well through a high pressure gun.</p> <p>The screens treated with STRIPPER 803 PASTA will have to be subsequently degreased through specific cleanser (DEGREASER VX) before use.</p>

STORAGE	
	<p>Keep the product in its original package, in a sheltered room.</p>

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk. While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.