



Screen Chemicals



## AUXILIARIES – GHOST IMAGE REMOVAL

### PRODUCTS FOR THE REMOVAL OF GHOST IMAGES

#### CLEANER STRIP PASTE

Code A31442045

**Product for the removal of “ghost images” after the recovery of the screens.**

#### PROPERTIES:

- Solvent - free
- Suitable for both polyester and nylon meshes
- Indicated for the removal of every kind of photoemulsion, provided that it has not been catalyzed and varnished
- Highly effective in the removal of “ghost images” and marks, originated by the “dyeing” action of the inks onto the screens

#### PREPARATION:

**CLEANER STRIP PASTE** is a ready-to-use product. It is recommended to mix the product, before using it.

#### APPLICATION:

- Apply the product through a sponge on the areas of the screen that are to be treated.
- Once the product has been applied, it is suggested to let it act during about 15 - 20 minutes. The action duration is related to the conditions of the mesh: the higher are the marks, the longer must be the action time. However, it mustn't be absolutely higher than 60 minutes. **CLEANER STRIP PASTE** is a caustic product, so it is recommended to work with the appropriate Individual Protection Devices. The combined action of **CLEANER STRIP PASTE** and **SOLVENT STRIP** is even more effective than the use of the single products.
- Remove well, through a high pressure nozzle.
- The screens, that have been treated with **CLEANER STRIP PASTE** must be subsequently degreased through specific cleansers (**CLEANSER 100**), before using them again.

Package: 1 and 5 Kg



**SOLVENT STRIP**

Code A31890945

**Product for helping the photoemulsion removal before treatment with the products of the series POLISTRIP. It may be used in a mixture with CLEANER STRIP PASTE (ratio 1:2), for the removal of “ghost images” after recovery of the screens.**

**PROPERTIES:**

- Suitable for both polyester and nylon meshes
- Emulsifiable with water

**PREPARATION:**

**SOLVENT STRIP** is a ready-to-use product.

**APPLICATION:**

**Removal of “ghost images”**

- Apply the product through a sponge on the areas of the screen that are to be treated.
- Once the product has been applied, it is suggested to let it act for a few minutes. The combined action of **CLEANER STRIP PASTE** and **SOLVENT STRIP** is even more effective than the use of the single products.
- Remove well, through a high pressure nozzle.
- The screens, that have been treated with **SOLVENT STRIP** must be subsequently degreased through specific cleansers (**CLEANSER 100**), before using them again.

**Photoemulsion removal**

- Apply the product on both sides of the screen through a sponge. The screen must have been previously cleaned from the traces of the ink used during printing.
- Scrub the surface, in order to help the product penetrating into the photoemulsion film.
- Let the product act for a few minutes.
- Once the product has been applied, let it act during 5 minutes.
- Remove the product, through a high pressure nozzle.
- The screens, that have been treated with **SOLVENT STRIP** must be subsequently degreased through specific cleansers (**CLEANSER 100**), before using them again.
- **SOLVENT STRIP** corrodes photoemulsions. So, do not use for the simple cleansing of the screens.

Package: 1 and 5 litres



<p><b>SOLVENTE 610</b> Code 152610</p> <p style="text-align: right;">Package: 1 and 5 litres</p>	<p><b>Product for the removal of “ghost images” and the possible traces of photo-emulsions after recovery of the screens (after treatment with the products of the series POLISTRIP).</b></p> <p><b>PROPERTIES:</b></p> <ul style="list-style-type: none"> <li>• Suitable for both polyester and nylon meshes</li> </ul> <p><b>PREPARATION:</b> <b>SOLVENTE 610</b> is a ready to use product.</p> <p><b>APPLICATION:</b> <b>Removal of possible residual photoemulsion.</b></p> <ul style="list-style-type: none"> <li>• Apply the product through a soft brush onto the areas of the screen.</li> <li>• Scrub the surface, in order to help the product penetration.</li> <li>• Once the product has been applied, let it act during 5-10 minutes.</li> <li>• Rinse off well, through a high pressure nozzle.</li> <li>• The screens, that have been treated with <b>SOLVENTE 610</b> must be subsequently degreased through specific cleansers (<b>CLEANSER 100</b>), before using them again.</li> </ul>
--	--

**SPECIAL INSTRUCTIONS**

- Always test the characteristics of the products, before starting application.

**IMPORTANT NOTE**

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising from the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.